



ESPECIFICACIONES DE LA REJA DE ACERO.

PANEL.

ALTURA.	ANCHO.	ABERTURA.	CALIBRE.		RESISTENCIA A LA RUPTURA.
m.	m.	mm.	Cal.	mm.	Lb/plg ²
0.63	2.50	50 x 200	6	4.89	75,000-100,000
1.00	2.50	50 x 200	6	4.89	75,000-100,000
1.50	2.50	50 x 200	6	4.89	75,000-100,000
2.00	2.50	50 x 200	6	4.89	75,000-100,000
2.50	2.50	50 x 200	6	4.89	75,000-100,000



POSTE.

ALTURA DEL PANEL.	ALTURA DEL POSTE.	CALIBRE.	DIMENCIONES.
m.	m.	mm.	Plg.
0.63	1.00	16	2 ¼ x 2 ¼
1.00	1.50	16	2 ¼ x 2 ¼
1.50	2.00	16	2 ¼ x 2 ¼
2.00	2.50	16	2 ¼ x 2 ¼
2.50	3.10	16	2 ¼ x 2 ¼



MALLA CICLÓNICA.

CALIBRES EN GALVANIZADO.
9
10.5
11
11.5
12.5
13
ALTURAS (dependiendo cal.)
1.00 mt.
1.25 mt.
1.50 mt.
1.75 mt.
2.00 mt.
2.50 mt.
3.00 mt.
4.00 mt.
ABERTURA (dependiendo cal.)
55 mm.
63 mm.
69 mm.

CALIBRES EN PLASTIFICADA.
10
11
12.5
ALTURAS.
1.00 mt.
1.25 mt.
1.50 mt.
1.75 mt.
2.00 mt.
ABERTURAS.
55 mm.



PROTECCIÓN DE NAVAJAS:

35 cm.	45 cm.	60 cm.
--------	--------	--------